



EMMA II™ Capnograph

Immediate capnography at your fingertips



Actual Size

- > **Immediate results** — EMMA requires virtually no warm-up time, with full accuracy in 15 seconds to measure end-tidal carbon dioxide (EtCO₂) and respiration rate (RR)
- > **Continuous capnogram** allows for confirmation of endotracheal tube placement, enables clinicians to assess the depth and effectiveness of compressions, and allows clinicians to recognize return of spontaneous circulation (ROSC)¹
- > **Small, portable capnograph** — lightweight design fits in the palm of your hand for unmatched mobility and convenience during short-term EtCO₂ monitoring of adult, pediatric, and infant patients
- > **Flexible use at multiple points of care**, including pre-hospital, emergency medicine, operating room, intensive care unit, and long-term acute care
- > **Helps clinicians assess the effectiveness of CPR and guide ventilation**, allowing them to make adjustments in the course of treatment, breath by breath
- > **Rugged, water-resistant design** for reliable operation in challenging environments
- > **Easy to maintain** — no routine calibration required

Web: www.englerusa.com / Email: info@englerusa.com
www.dynaxusa.com / www.ez-stretcher.com / www.ez-dentaltable.com /
www.25KSeries.com for brochures, manuals and “how to”
pages please visit www.engler411.com

Engler Engineering Corporation
1099 East 47th Street - Hialeah, Florida 33013 USA
Tel: (800) 445-8581 / (305) 688-8581 / Fax: (305) 685-7671



FEATURES

- > Clear, continuous capnogram of carbon dioxide values
- > Simple, easy-to-use interface for quick set-up and one-touch programming
- > Audible and visual alarm system for No Adapter, Clogged Adapter, No Breath (Apnea), Low Battery and adjustable High and Low EtCO₂ alarm
- > Long battery life—up to 10 hours of normal use with two standard AAA lithium batteries

For Optimum performance; the Energizer Ultimate Lithium Ion L92 AAA battery is recommended

Alarm Limits

Alarm limits and visual alarm status indicator, silence active alarms for two minutes

Capnogram

14.4 second sweep of CO₂ values

Power Button

Warm-up time to full accuracy in 15 seconds

End-tidal Carbon Dioxide

Quantitative EtCO₂ is updated every breath (Model 3678 displays in kPa)

Respiration Rate

RR is displayed after two breaths and updated every breath

Airway Adapter

Available in adult/pediatric and infant sizes



PERFORMANCE

RANGES	ENVIRONMENTAL
CO ₂ 0-99 mmHg 0-9.9 kPa	Operating temperature -5 to 50° C (23 to 122° F)
RR..... .3-150 bpm	Operating atmospheric pressure 70 to 120 kPa
ACCURACY (STANDARD CONDITIONS)	Operating humidity..... 10-95%, non-condensing
CO ₂ 0-40 mmHg ±2 mmHg; 41-99 mmHg 6% of reading 0-5.3 kPa ±0.3 kPa; 5.4-9.9 kPa 6% of reading	Storage temperature -30 to 70° C (-22 to 158° F)
RR..... ±1 bpm	Storage atmospheric pressure 50 to 120 kPa
BATTERIES	PHYSICAL CHARACTERISTICS
Type..... 2 (two) AAA Cell Alkaline or Lithium	Dimensions 2.1 x 1.5 x 1.5" (5.2 x 3.9 x 3.9 cm)
Battery life..... 6 hours (Alkaline) 10 hours (Lithium)	Weight 2.1 oz (59.5 g) (with Alkaline batteries)
	ADAPTER INFORMATION
	Dead space adult/pediatric..... .6 ml
	Dead space infant 1 ml

KIT



- > EMMA Kit*

ACCESSORIES



- > EMMA Airway Adapter

Adult/Pediatric
Box of 25



- > EMMA Airway Adapter

Infant
Box of 10

*In order for the EMMA Kit to provide readings, either of the listed airway adapters is required. Kit includes EMMA, pouch, and lanyard.

Caution: Federal law restricts this device to sale by or on the order of a physician.

NOT AVAILABLE FOR EXPORT SALES MUST BE DROP SHIPPED BY ENGLER TO U.S. CUSTOMERS ONLY