


FRICITION GRIP DRILLING ACCESSORIES

CARBIDE BUR No.	2	4	6	35	37	702
 <p>P-131 F. G CARBIDE BURS 1.60 mm X 19 mm L</p>						
HEAD SHAPE	ROUND	ROUND	ROUND	INVERTED CONE	INVERTED CONE	CROSS-CUT TAPERED FISSURE
HEAD SIZE (1/10 mm)	010	014	018	010	014	021
DESCRIPTION	- DRILLING RESULTING IN ROUND BOTTOM - TOOTH REDUCTION PROCEDURES - FINISHING & TRIMMING WITH LIGHT TOUCH	- DRILLING RESULTING IN ROUND BOTTOM - TOOTH REDUCTION PROCEDURES - FINISHING & TRIMMING WITH LIGHT TOUCH	- DRILLING RESULTING IN ROUND BOTTOM - TOOTH REDUCTION PROCEDURES - FINISHING & TRIMMING WITH LIGHT TOUCH	- DRILLING RESULTING IN SQUARE BOTTOM - TOOTH REDUCTION PROCEDURES - FINISHING & TRIMMING WITH LIGHT TOUCH	- DRILLING RESULTING IN SQUARE BOTTOM - TOOTH REDUCTION PROCEDURES - FINISHING & TRIMMING WITH LIGHT TOUCH	- SECTIONING TEETH FOR EXTRACTION - TOOTH REDUCTION PROCEDURES - FINISHING & TRIMMING WITH LIGHT TOUCH

F. G. CARBIDE BURS (KIT OF 6)



PART # P-131

SET OF 6 ASSORTED FRICTION GRIP CARBIDE BURS 1.60 MM SHANK DIAMETER. FITS INTO OPTIONAL CONTRA ANGLE FOR DRILLING DENTAL PROCEDURES. WHEN DRILLING IRRIGATION WITH WATER IS RECOMMENDED.

F. G. CONTRA ANGLE FOR HANDPIECE



PART # P-A3

THIS FRICTION GRIP CONTRA ANGLE FOR STRAIGHT HANDPIECE ACCEPTS 1.60 MM FRICTION GRIP CARBIDE OR DIAMOND BURS (SOLD SEPARATELY) FOR DRILLING. DAILY OILING AND CLEANING REQUIRED. SUPPLIED WITH A 30 DAY WARRANTY. (AUTOCLAVABLE)

F. G. CONTRA ANGLE FOR MICROMOTOR



PART # P-A4

THIS FRICTION GRIP CONTRA ANGLE FOR MICROMOTOR ACCEPTS 1.60 MM FRICTION GRIP CARBIDE OR DIAMOND BURS (SOLD SEPARATELY) FOR DRILLING. DAILY OILING AND CLEANING REQUIRED. SUPPLIED WITH A 30 DAY WARRANTY. (AUTOCLAVABLE)